



Bush Cutter George

Tackle giant weeds and long grass with ease with this super manoeuvrable flail head, stand-on controlled, rubber-tracked brushcutting machine!



SPECIFICATIONS Bush Cutter George

Engine	44 HP Kubota Diesel HST with electric start
Output	33.0kW / 44.8psPS
Displacement (cc)	2197 cm3 (44.8PS)/2600rpm
Torque (Net)	145.1 Nm (14.5kgf.m)1500rpm
Fuel type	Diesel
Fuel Capacity (L)	52
Ground Speed (Km/hr)	Forward Hi 0-9km/h Low 0-6km/h Reverse Hi 0-9km/h Low 0-4.5km/h
Transmission	Continuously variable
Brakes	Hydraulic
Steering	Twin HST
Turning Radius (mm)	2000
Weight (kg)	2000
Overall Dimensions (cm)	3465L x 1700W x 1405H
Cutting Height (mm)	0-320
Cutting Width (mm)	1545
Cutting System	Flail with 80 Pairs
Gradeability	35 degrees
Stability Angle	Left/Right 40 degrees

FEATURES

Durable flails separate on shackles to reduce impact damage on blades and resist brush tangling.

Operator platform and control deck automatically levels out on slopes to reduce fatigue and increase safety.

Side shifting cutter head slides up to 500mm to reach previously inaccessible brush.

Exhaust fan periodically switches direction to expel accumulated brush, preventing overheating.

Rotor cuts in forward and reverse. Equipped with chain to prevent projectile objects. The hydraulic system runs the rotor cut head.

An automatically levelling control deck and operator platform reduce fatigue and increase operator safety when operating on slopes.

Safety features - A control stick to manoeuvre securely. if you release the control, it comes automatically to neutral position.

www.therazorback.com.au

razorback brushcutters

razorback_allterrain_mower